



HIGHLIGHTS AT A GLANCE:

- Compact 9-pin narrow carriage printer
- Up to 400 characters per second
- Ideal for airport applications
- Solution designed for airport counters
- Roll support clipped and attached to the printer
- Excellent paper holding
- 7 million character long capacity ribbon



1140 Roll Holder

Based on the proven quality of the Tally Dascom 1140 the roll holder version is specially designed for roll paper applications that can be found on airports, railways and travel agencies.

Easy installation

The support has been designed to be set up by any user. The user just clips while being firmly fixed and connect the equipotential bonding to the printer chassis.

User friendly operation

Made of metal, it will easily withstand rough handling by users and can works with roll up to 2 kilogram. When exchanging the paper roll the axle won't be lost as it is fixed to the mechanism.

Space saving

No additional footprint required as the roll holder is fixed on the printer. The back of the printer can be positioned at the edge of the desk and the roll media will not be affected. Users will be able to move the printer without worrying about the roll support because it is attached to the printer.



TECHNICAL DATA

Print Speed	Fastest Speed: Character density HS Draft Draft NLO	400 cps 10 / 12 / 15 cpi 400 / 360 / 300 cps 300 /360 / 300 cps 75 / 90 /75 cps
Resolution	up to 144 x 240 dpi	
Throughput	290 pages per hour	
Character Density	10, 12, 15, 17.1, 20 cpi	
Line Density	1, 2, 3, 4, 6, 8 lpi	
Print head Life	400 million strokes	
Memory	up to 256 kB	
Standard Connectivity	USB 2.0	
Optional Connectivity	Parallel IEEE 1284. Serial RS-232C, Ethernet (10/100)	
Emulation	IBM ProPrinter2380 Plus, Epson ESC P/2	
Fonts	Draft, Quadrato, Courier, HS Draft, OCR-A/B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET	
Consumables	Ribbon: 7 million characters	
Paper Handling	Roll paper	
Number of Copies	1 original + 4 copies	
Paper Type	Continuous paper rolls, mulit-part forms Max. roll diameter: 130 mm / 2 kg Min. core paper roll: 20 mm	
Paper Weight	52 - 100 g/m ²	
Paper Size	Width: 75 to 220 mm	
Physical Weight	5 kg	
Physical Size	369 x 283 x 130 mm (W x D x H)	
Acoustic	57 dB(A)	
Power Voltage	100-230 V - 50/60 Hz	
Power Consumption	less then 1,2 Watt Sleep Mode	
Temperature	+5° to +35° C; 10% to 80% humidity	
Workload	6.000 pages per month	
MTBF	12.000 hours	
Driver	Windows 8/ 8.1/10/11 and Server 2012/2016/2019/2022	

DASCOM Europe GmbH

Heuweg 3 | 89079 Ulm | GERMANY Tel.: +49 731 2075-0 | Fax: +49 731 2075-100 info@dascom.com | www.dascomeurope.de DASCOM GB Ltd

Hart House, Priestley Road Basingstoke | Hampshire RG24 9PU | ENGLAND Tel.: +44 1256 355 130| Fax: +44 1256 481 400 info.gb@dascom-com | www.dascom.co.uk DASCOM (Holdings) LTD.

R. 1811-1816A | Nan Fung Centre 264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong Tel.: +852 2498 1507 | Fax: +852 2413 6047

