

1330
Compact and fast



HIGHLIGHTS AT A GLANCE:

- Advanced 24-pin, 82-Column flatbed printer
- Up to 450 cps speed
- Ideal for front and back office application
- Up to 7-parts copy capability
- Intelligent print position tracking sensor

1330

The 1330 is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's surgeries where space is limited. It is equipped with a linear encoder sensor to position the print head with high accuracy and intellectually detect and correct any misplaced carriage, which ensures good printing quality and significantly reduces the chances of errors in printing

Using the long life ribbon option, the 1330 requires fewer ribbon changes, less downtime and lower running costs. With print speeds of up to 450 characters per second (cps) and flexible media handling, it keeps transactions smooth and the user happy. The 1330 is a reliable and easy to use printer, with low running costs and a small footprint..

TECHNICAL DATA

Print Speed	Fastest Speed: 600 cps Character density: 10 / 12 / 15 cpi <i>Draft</i> : 300 / 360 / 450 cps <i>NLQ</i> : 200 / 240 / 300 cps <i>LQ</i> : 100 / 120 / 150 cps
Resolution	up to 360 x 360 dpi
Character Density	10, 12, 15, 16.6, 17.1, 20, 24 cpi
Line Density	1/6 inch, programmable in 1/360 inch increments
Printhead Life	400 million strokes per pin
Memory	up to 256 kB
Standard Connectivity	USB 2.0
Optional Connectivity	Parallel (IEEE 1284), Serial (RS-232C), Ethernet
Emulation	Epson ESC P/2, IBM PPDS
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 10 Barcodes
Consumables	Ribbon: 7 million characters
Paper Handling	Friction and push tractor
Number of Copies	1 original + 6 copies
Paper Type	Cut sheets, Continuous forms, multi-part forms
Paper Weight	52-120 g/m ²
Paper Size	Width: 55 to 297 mm (Cut Sheet)
Physical Weight	4,2 kg
Physical Size	395 x 320 x 205 mm (W x D x H)
Acoustic	<57 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	5,9 Watt Stand-By
Temperature	5° to +35° C; 10% to 95% humidity
Workload	6.000 pages per month
MTBF	12.000 hours
Drivers	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022

Configurations:

- **1330** Standard model
- **1330 PAR** Model with USB and parallel interface
- **1330 SER** Model with USB and serial interface
- **1330 ETH** Model with USB and Ethernet interface

DASCOM GB Ltd
Hart House, Priestley Road
Basingstoke | Hampshire RG24 9PU | ENGLAND
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400
info.gb@dascom-com | www.dascom.co.uk

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047