



2610+

High performance at low cost





HIGHLIGHTS AT A GLANCE:

- Print speed up to 683 cps
- Up to 20.000 pages/month
- 136 columns / A3
- 24 wires print head for excellent print quality
- Straight paper path for easy paper handling
- Metal tear bar
- Ethernet with IPv6 support, parallel and USB interface as standard
- USB Host interface for easy firmwareupdate
- User-friendly, backlit illuminated LC display



2610+

The new Tally Dascom 2610+ is the **further developed variant** of the successful Tally Dascom 2610.

Thanks to the two-part upper cover, the printed pages can now be removed even more easily from the end of the book. A **metal tear bar** ensures that even thicker paper or multiple sets are separated cleanly. The **durable ribbon for 15 million characters** can easily be replaced. The new ribbon mask ensures that the ribbon is inserted correctly. In addition to the standard interfaces **USB, Parallel and Ethernet** (with IPv6 support), the Tally Dascom 2600+ now also has a **USB host interface**, so that new firmware can easily be installed with the help of a USB stick.

The new print head is not only **up to 20% faster**, but also allows for a **noise reduction of up to 2 decibels** thanks to its design.

TECHNICAL DATA

	683 cps 10 / 12 / 15 cpi	
•	10 / 12 / 13 срі 600 / 683 / 683 срs	
	513 / 513 / 513 cps	
NLQ	228 / 273 / 171 cps	
LO	114 / 137 / 171 cps	
Up to360 x 360 dpi		
457 pages per hour		
10, 12, 15, 17.1, 20 cpi		
2, 3, 4, 6, 8, 12 lpi		
500 Mio. impact per w	ire	
256 kB		
Parallel (Bi-directional) USB Host), USB 2.0 and Ethernet (10/100BaseT, IPv6)	
Serial RS-232		
Tally WebPanel via Ethernet; Config-Tool via USB/Parallel		
	IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP	
•	Epson FX 9-Nadel Emulation	
• • • • • • • • • • • • • • • • • • • •		
HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing		
Ribbon: 15 Mio. charac	eters	
	push (front or rear) or pull (top) version, continuous paper th and park position, cut sheet front insertion, tear or front off	
Additional push tracto	r (rear)	
Push tractor front: 1 or		
	·	
	s forms, multi-part forms	
Width: 76 to 420 mm; Length: 76 to 599 mm		
10,6 kg		
600 x 265 x 200 mm (V	V x D x H)	
,		
<53 dB(A)		
·	19	
<53 dB(A)		
<53 dB(A) 100 - 240 V autosensir	V Sleep Mode	
<53 dB(A) 100 - 240 V autosensin 60 Watt printing; <3 W	V Sleep Mode o 85% rel. humidity	
<53 dB(A) 100 - 240 V autosensin 60 Watt printing; <3 W +10° to +40° C; 10% to	V Sleep Mode o 85% rel. humidity th	
	Up to 360 x 360 dpi 457 pages per hour 10, 12, 15, 17.1, 20 cpi 2, 3, 4, 6, 8, 12 lpi 500 Mio. impact per w 256 kB Parallel (Bi-directional USB Host Serial RS-232 Tally WebPanel via Eth IBM ProPrinter XL24, Epson FX 9-Nadel Emu LA Upgrade Kit: DEC HS Draft, Draft, Courie and large character pri Ribbon: 15 Mio. charact One tractor usable as with straight paper pa Additional push tracto Push tractor front: 1 or Pull tractor top: 1 origi Cut sheet: 1 original + Cut sheets, continuous 60-120 g/m² Width: 76 to 420 mm; 10,6 kg	

Configuration:

• 2610+ Standard model

