

DL-210/310

The fast
entry-level variant



HIGHLIGHTS AT A GLANCE:

- Easy and Quick media loading
- Variety of interfaces
- Supports ZPL and EPL emulation
- Optional Cutter
- 300 m ribbon and 5 inch (127 mm) media capacity



DL-210/310

Tally Dascom's DL-210 thermal transfer printer offers reliability, precision and performance in desktop size.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media and ribbon loading. The clear panel enable simple and effective operation making it very simple to use.

The DL-210 is easily integrated into existing systems as there are several interfaces also available. In addition to this, the DL-210 is also available with an optional cutter to meet industry requirements.

TECHNICAL DATA

Print Speed	DL-210: 6 ips (152 mm/sec.) DL-310: 4 ips (102 mm/Sek.)
Print Width	DL-210: 108 mm DL-310: 102 mm
Print Method	Direct Thermal or Thermal Transfer
Resolution	DL-210: 203 dpi DL-310: 300 dpi
Fonts	Font A - Font V (ZPL) User defined fonts can be downloaded into FLASH/SDRAM
Printhead Lifetime	30 km or 6 months
Memory	DL-210: 8 MB Flash, 8 MB SDRAM DL-310: 8 MB Flash, 16 MB SDRAM
Interfaces Standard	USB (2.0 Full Speed)
Interfaces Optional	Serial (RS-232C), Parallel (IEEE 1284), Ethernet (10/100)
Emulations	ZPL II, EPL
Consumables	Ribbon, Direct Thermal/ Thermal Transfer paper and labels
Ribbon	Width: 33 - 110 mm; Length: 300 m Core diameter: 1" (25,47 mm); Outside diameter: 68 mm
Media	Width: 25 - 118 mm; Thickness: 0,06 - 0,18 mm Core diameter: 1" or 1,5" (25,4 mm or 37 mm); Outside diameter: 5" (127 mm)
Sensors	Black Mark, Label Gap, Farbband
Barcode	1D: Code 11, Interleaved 2-of-5, Code 39, Code 49, Code 93, Code 128, Planet Code, EAN 8, EAN 13, UPC-E, UPC-A, Industrial 2 of 5, Standard 2 of 5, Codabar, MSI, Plessey 2D: PDF 417, MaxiCode, QR Code, Data Matrix
Physical Weight	3 kg
Physical Size	230 x 290 x 176 mm (W x D x H)
Power Voltage	100 - 240 V AC - 50/60 Hz
Temperature	+5° to +40° C
Humidity	10% to 98% (non condensing)
Print Volume	up to 300 m/day
Printer Driver	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022
Options	Models with cutter or peeler; Serial, Parallel, Ethernet interface

Configurations:

- **DL-210/310** Standard product (USB only)
- **DL-210/310 Ser** Model with USB & ser. interface
- **DL-210/310 Par** Model with USB & par. interface
- **DL-210/310 Eth** Model with USB & Ethernet interface

DASCOM GB Ltd
Hart House, Priestley Road
Basingstoke | Hampshire RG24 9PU | ENGLAND
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400
info.gb@dascom-com | www.dascom.co.uk

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047