

# 1330

Compact and fast



#### HIGHLIGHTS AT A GLANCE:

- Advanced 24-pin, 82-Column flatbed printer
- Up to 450 cps speed
- Ideal for front and back office application
- Up to 7-parts copy capability
- Intelligent print position tracking sensor

# 1330

The 1330 is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's surgeries where space is limited. It is equipped with a linear encoder sensor to position the print head with high accuracy and intellectually detect and correct any misplaced carriage, which ensures good printing quality and significantly reduces the chances of errors in printing

Using the long life ribbon option, the 1330 requires fewer ribbon changes, less downtime and lower running costs. With print speeds of up to 450 characters per second (cps) and flexible media handling, it keeps transactions smooth and the user happy. The 1330 is a reliable and easy to use printer, with low running costs and a small footprint..

## TECHNICAL DATA

<b>Print Speed</b>	Fastest Speed: 600 cps Character density 10 / 12 / 15 cpi <i>Draft</i> 300 / 360 / 450 cps <i>NLQ</i> 200 / 240 / 300 cps <i>LQ</i> 100 / 120 / 150 cps
<b>Resolution</b>	up to 360 x 360 dpi
<b>Character Density</b>	10, 12, 15, 16.6, 17.1, 20, 24 cpi
<b>Line Density</b>	1/6 inch, programmable in 1/360 inch increments
<b>Printhead Life</b>	400 million strokes per pin
<b>Memory</b>	up to 256 kB
<b>Standard Connectivity</b>	USB 2.0
<b>Optional Connectivity</b>	Parallel (IEEE 1284), Serial (RS-232C), Ethernet
<b>Emulation</b>	Epson ESC P/2, IBM PPDS
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 10 Barcodes
<b>Consumables</b>	Ribbon: 7 million characters
<b>Paper Handling</b>	Friction and push tractor
<b>Number of Copies</b>	1 original + 6 copies
<b>Paper Type</b>	Cut sheets, Continuous forms, multi-part forms
<b>Paper Weight</b>	52-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 55 to 297 mm (Cut Sheet)
<b>Physical Weight</b>	4,2 kg
<b>Physical Size</b>	395 x 320 x 205 mm (W x D x H)
<b>Acoustic</b>	<57 dB(A)
<b>Power Voltage</b>	230 V - 50/60 Hz
<b>Power Consumption</b>	5,9 Watt Stand-By
<b>Temperature</b>	+5° to +40° C; 10% to 85% rel. humidity
<b>Workload</b>	6.000 pages per month
<b>MTBF</b>	12.000 hours
<b>Drivers</b>	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022

### Configurations:

- **1330** Standard model
- **1330 PAR** Model with USB and parallel interface
- **1330 SER** Model with USB and serial interface
- **1330 ETH** Model with USB and Ethernet interface

**DASCOM GB Ltd**  
Hart House, Priestley Road  
Basingstoke | Hampshire RG24 9PU | ENGLAND  
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400  
info.gb@dascom-com | www.dascom.co.uk

**DASCOM Europe GmbH**  
Heuweg 3 | 89079 Ulm | GERMANY  
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100  
info@dascom.com | www.dascomeurope.de

**DASCOM (Holdings) LTD.**  
R. 1811-1816A | Nan Fung Centre  
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong  
Tel.: +852 2498 1507 | Fax: +852 2413 6047