



1140 Roll Holder

Compact in size



HIGHLIGHTS AT A GLANCE:

- Compact 9-pin narrow carriage printer
- Up to 400 characters per second
- Ideal for airport applications
- Solution designed for airport counters
- Roll support clipped and attached to the printer
- Excellent paper holding
- 7 million character long capacity ribbon

1140 Roll Holder

Based on the proven quality of the Tally Dascom 1140 the roll holder version is specially designed for roll paper applications that can be found on airports, railways and travel agencies.

Easy installation

The support has been designed to be set up by any user. The user just clips while being firmly fixed and connect the equipo-
tential bonding to the printer chassis.

User friendly operation

Made of metal, it will easily withstand rough handling by users and can works with roll up to 2 kilogram. When exchanging the paper roll the axle won't be lost as it is fixed to the mechanism.

Space saving

No additional footprint required as the roll holder is fixed on the printer. The back of the printer can be positioned at the edge of the desk and the roll media will not be affected. Users will be able to move the printer without worrying about the roll sup-
port because it is attached to the printer.



TECHNICAL DATA

Print Speed	Fastest Speed: 400 cps Character density 10 / 12 / 15 cpi HS Draft 400 / 360 / 300 cps Draft 300 / 360 / 300 cps NLQ 75 / 90 / 75 cps
Resolution	up to 144 x 240 dpi
Throughput	290 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Print head Life	400 million strokes
Memory	up to 256 kB
Standard Connectivity	USB 2.0
Optional Connectivity	Parallel IEEE 1284, Serial RS-232C, Ethernet (10/100)
Emulation	IBM ProPrinter2380 Plus, Epson ESC P/2
Fonts	Draft, Quadrato, Courier, HS Draft, OCR-A/B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Consumables	Ribbon: 7 million characters
Paper Handling	Roll paper
Number of Copies	1 original + 4 copies
Paper Type	Continuous paper rolls, mulit-part forms Max. roll diameter: 130 mm / 2 kg Min. core paper roll: 20 mm
Paper Weight	52 - 100 g/m ²
Paper Size	Width: 75 to 220 mm
Physical Weight	5 kg
Physical Size	369 x 283 x 130 mm (W x D x H)
Acoustic	57 dB(A)
Power Voltage	100-230 V - 50/60 Hz
Power Consumption	less then 1,2 Watt Sleep Mode
Temperature	+5° to +40° C; 10% to 85% rel. humidity
Workload	6.000 pages per month
MTBF	12.000 hours
Driver	Windows 8/ 8.1/10/11 and Server 2012/2016/2019/2022

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM GB Ltd
Hart House, Priestley Road
Basingstoke | Hampshire RG24 9PU | ENGLAND
Tel.: +44 1256 355 130| Fax: +44 1256 481 400
info.gb@dascom-com | www.dascom.co.uk

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047

All company and product names are trademark of theri respective owner. Copyright © 2025 DASCOM. Specification are subject to change without notice.
Subject to modification, of error or misprint.

DASCOM